

## H 1850 STORE - PARK

	Capacity	Standard travel	Useful height	Max. car dimensions	Clearance between columns (*)	Standard Platform into pit	Standard lower platform
2 LEVELS WITHOUT PIT	2000 kg.	1850 mm	1800 mm	2200x5000 mm	2300 mm	0 mm	2200 x 3860 mm
	4405 lbs	72,8 inch	70,9 inch	86,6x196,8 inch	90,6 inch	0 inch	86,6x152 inch
2 LEVELS WITH 1 IN PIT	2000 kg.	1850 mm	1800 mm	2200x5000 mm	2300 mm	2200x5000 mm	2200 x 3860 mm
	4405 lbs	72,8 inch	70,9 inch	86,6x196,8 inch	90,6 inch	86,6x196,8 inch	86,6x152 inch
3 LEVELS WITH 1 IN PIT	2000 kg.	1850 mm	1800 mm	2200x5000 (4800) mm	2300 mm	2200x5000 mm	2200 x 5000 mm
	4405 lbs	72,8 inch	70,9 inch	86,6x196,8 (189) inch	90,6 inch	86,6x196,8 inch	86,6x197 inch

	Standard upper platform	Pit	Moving power supply	Lifting power supply	Ascent / descent time	Electricity power
2 NIVEAUX	2200 x 5700 mm	0 mm	0,35 kw	2,2/3,5 kw	30 /30 s	400 v / 50 hz
	86,6x224,4 inch	0,0 inch	0,5 hp	3/5 hp	30 /30 s	400 v / 50 hz
2 NIVEAUX + FOSSE	2200 x 5700 mm	2200 mm	0,35 kw	2,2/3,5 kw	30 /30 s	400 v / 50 hz
	86,6x224,4 inch	86,64 inch	0,5 hp	3/5 hp	30 /30 s	400 v / 50 hz
3 NEVEAUX + FOSSE	2200 x 5700 mm	2200 mm	0,35 kw	2,2/3,5 kw	30 /30 s	400 v / 50 hz
	86,6x224,4 inch	86,64 inch	0,5 hp	3/5 hp	30 /30 s	400 v / 50 hz

## H 2100 STORE - PARK

	Capacity	Standard travel	Useful height	Max. car dimensions	Clearance between columns (*)	Standard Platform into pit	Standard lower platform
2 NIVEAUX	2005 kg.	2100 mm	2050 mm	2200x5000 mm	2300 mm	0 mm	2200 x 3860 mm
	5511 lbs	82,74 inch	80,74 inch	86,6x196,8 inch	90,6 inch	0 inch	86,6x152 inch
2 NIVEAUX + FOSSE	2005 kg.	2100 mm	2050 mm	2200x5000 mm	2300 mm	2200x5000 mm	2200 x 3860 mm
	5511 lbs	82,74 inch	80,74 inch	86,6x196,8 inch	90,6 inch	86,6x196,8 inch	86,6x152 inch
3 NEVEAUX + FOSSE	2005 kg.	2100 mm	2050 mm	2200x5000 (4800) mm	2300 mm	2200x5000 mm	2200 x 5000 mm
	5511 lbs	82,74 inch	80,74 inch	86,6x196,8 (189) inch	90,6 inch	86,6x196,8 inch	86,6x197 inch

	Standard upper platform	Pit	Moving power supply	Lifting power supply	Ascent / descent time	Electricity power
2 NIVEAUX	2200 x 5700 mm	0 mm	0,35 kw	2,2/3,5 kw	34 /34 s	400 v / 50 hz
	86,6x224,4 inch	0,0 inch	0,5 hp	3/5 hp	34 /34 s	400 v / 50 hz
2 NIVEAUX + FOSSE	2200 x 5700 mm	2450 mm	0,35 kw	2,2/3,5 kw	34 /34 s	400 v / 50 hz
	86,6x224,4 inch	96,54 inch	0,5 hp	3/5 hp	34 /34 s	400 v / 50 hz
3 NEVEAUX + FOSSE	2200 x 5700 mm	2450 mm	0,35 kw	2,2/3,5 kw	34 /34 s	400 v / 50 hz
	86,6x224,4 inch	96,54 inch	0,5 hp	3/5 hp	34 /34 s	400 v / 50 hz