

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	TOTALREX 30 GOLD	TOTALREX 30 GOLD + T	TOTALREX 25 GOLD + TP	TOTALREX 30 GOLD F	TOTALREX GOLD 30 +TF	TOTALREX GOLD 25 +TPF	NOTE
standard Color BLUE RAL 5005 and SILVER RAL 7040	■	■	■	■	■	■	
Nr. 1 Standard platform with electrostatics galvanized smooth staves	■	■	■	■	■	■	
Max. travel 4.100 mm.	■	■	■	■	■	■	
Flanged scissor				■	■	■	
Nr. 2 bases for pit fixing	■	■	■	■	■	■	
Nr. 2 Lifting Cylinders	■	■	■	■	■	■	
Nr. 1 "Dead man present" push button board with key on top of the platform - residential design - IP 54	■	■	■	■	■	■	
N. 2 push button board - residential design "dead man present" with key, at floors IP 54	■	■	■	■	■	■	
Security control module for sensors and safety locks	■	■	■	■	■	■	
N. 2 Electromagnetic sensors or N. 2 safety mechanical locks	■	■	■	■	■	■	
Nr. 2 photocells barriers H=600 mm., for car movement back and forward	■	■	■	■	■	■	
Emergency auto dialer	■	■	■	■	■	■	Based on norm EN 81 - 28
N. 1 acoustic warning	■	■	■	■	■	■	
Nr. 1 hydraulic pump with motor	■	■	■	■	■	■	
Nr. 1 Electrical panel board	■	■	■	■	■	■	
standard power supply 230-400 V/3Ph/50 Hz- 460 V/3Ph/60 Hz	■	■	■	■	■	■	
N. 2 stopping wheels L = 745 mm	■	■	■	■	■	■	
2 stops	■	■	■	■	■	■	
Transittable roof 3.000 Kg max - not suitable for lifting vehicles		■			■		Roof transittability: max. 3000 kg. (Not suitable for lifting vehicle)
Tileable roof in smooth metal sheet with tray of 30 mm. for lining			■			■	Roof transittability: max. 3000 kg. (Not suitable for lifting vehicle) Tiles weight allowed max 70 Kg / m ² ; Pit has been modified for tile thickness
Nylon package	■	■	■	■	■	■	
Anchors screws	■	■	■	■	■	■	
Emergency push button with key for pit access	■	■	■	■	■	■	
Non standard platform	□	□	□	□	□	□	
Hot dip galvanized staves for standard platform	□	□	□	□	□	□	
Hot dip galvanized staves for non standard platform	□	□	□	□	□	□	
Tileable platform predisposition	□			□			Tiles weight max 70 Kg /m ² ; Pit has been modified for tiles thickness. Add bearing wheels kit for intensive use
bearing wheel for intensive use	□	□	□	□	□	□	advised for 10 cycles a day and for roof versions
Loading capacity up to 4.000 Kg	□	□	□	□	□	□	
Additional stop (third stop)	□	□	□	□	□	□	
additional push button board residential design	□	□	□	□	□	□	
Additional push button board with upright support for double entrance and exit - residential design							
stainless steel push button board	□	□	□	□	□	□	

