

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	TOTALREX 60 PLATINUM	TOTALREX 40 PLATINUM + T	TOTALREX 35 PLATINUM + TP	NOTE
standard Color BLUE RAL 5005 and SILVER RAL 7040	■	■	■	
Nr. 1 Standard platform with electrostatics galvanized smooth staves	■	■	■	
Max. travel 4.200 mm.	■	■	■	
Nr. 2 bases for pit fixing	■	■	■	
Nr. 4 Lifting Cylinders	■	■	■	
Nr. 1 "Dead man present" push button board with key on top of the platform - residential design - IP 54	■	■	■	
N. 2 push button board - residential design "dead man present" with key, at floors IP 54	■	■	■	
Security control module for sensors and safety locks	■	■	■	
N. 2 Electromagnetic sensors or N. 2 safety mechanical locks	■	■	■	
Nr. 2 photocells barriers H=600 mm., for car movement back and forward	■	■	■	
Emergency auto dialer	■	■	■	Based on norm EN 81 - 28
N. 1 acoustic warning	■	■	■	
Nr. 1 hydraulic pump with motor	■	■	■	
Nr. 1 Electrical panel board	■	■	■	
standard power supply 230-400 V/3Ph/50 Hz- 460 V/3Ph/60 Hz	■	■	■	
N. 2 stopping wheels L = 745 mm	■	■	■	
2 stops	■	■	■	
Transittable roof 3.000 Kg max - not suitable for lifting vehicles		■		Roof transittability: max. 3000 kg. (Not suitable for lifting vehicle)
Tileable roof in smooth metal sheet with tray of 30 mm. for lining			■	Roof transittability: max. 3000 kg. (Not suitable for lifting vehicle) Tiles weight allowed max 70 Kg / m2 ; Pit has been modified for tile thickness
bearing wheel for intensive use	■	■	■	
Nylon package	■	■	■	
Anchors screws	■	■	■	
Emergency push button with key for pit access	■	■	■	
Non standard platform	□	□	□	
Additional cost for non standard roof		□	□	
Additional stop (third stop)	□	□	□	
additional push button board residential design	□	□	□	
Additional push button board with upright support for double entrance and exit - residential design	□	□	□	
stainless steel push button board	□	□	□	
Additional push button board with upright support for double entrance and exit - residential design in stainless steel	□	□	□	
additional electromagnetic sensor	□	□	□	
Additional mechanical safety lock	□	□	□	Control for manual doors
Predisposition for electromechanical safety lock Kronenberg or Prudhomme	□	□	□	Control for manual doors
Outside pulse call for each push button board	□	□	□	Applicable on a enclosed shaft
Automatic repositioning platform at home position (just with pulse call option)	□	□	□	Applicable on a enclosed shaft
Automatic repositioning platform in case of fire	□	□	□	Applicable on a enclosed shaft
Receiver for remote control use	□	□	□	Operational distance max. 5 m
Transmitter for remote control use	□	□	□	Operational distance max. 5 m
Flashing light	□	□	□	
Siren	□	□	□	
Traffic light (two colors)	□	□	□	

Traffic light (two colors) residential design	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Waterproof galvanized cover for control unit for outdoor installation	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Increasing lifting speed from 0,06 to 0,12 mt/sec.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Led lights at low tension on board		<input type="checkbox"/>	<input type="checkbox"/>	
Soft Starter	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Hydraulic pump with low acoustic emission	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	On request
Nr. 1 fix handrail H=1.200 mm. (per meter)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 1 removable handrail H= 1.200 mm (per meter)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Photocells barriers for doors area control H= 150 mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Photocells barriers for doors area control H= 300 mm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 2 photocells barriers H=900 mm., for car movement back and forward	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Including supporting columns
Nr. 2 photocells barriers H=1200 mm., for car movement back and forward	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 2 photocells barriers H=1500 mm., for car movement back and forward	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 2 photocells barriers H=1800 mm., for car movement back and forward	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Supporting structure for photocells barriers (H=1200, 1500, 1800 mm)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
GSM interface with 20 mt. length cable.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
N. 2 photocells barriers for top roof control		<input type="checkbox"/>	<input type="checkbox"/>	
Laser scanner	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
GSM interface with 20 mt. length cable.	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Kit n. 4 platform ground supports	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
non standard Color	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	On request
non standard power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting totalrex Platinum	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + roof and support structure powered coated painting		<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting for non standard platform	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon + powered coated painting non standard roof	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization (Platform, bases and scissor)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization for roof and support structure		<input type="checkbox"/>	<input type="checkbox"/>	
Additional cost for hot dip galvanization non standard platform	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Additional cost for hot dip galvanization non standard roof	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Platform on pallet	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Control panel crate	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	