

TOTALREX

	Capacity	Standard Lifting Height	Max Lifting Height	Minimum Platform	Standard Platform	Max Platform	Distanza Pedana	Pit	Power	Speed	Power supply	Standard Weight	Notes
TOTAL REX PF	3.000 kg.	3.500 mm	3.500 mm	2320x4700 mm	2850x5200 mm	3000x5600 mm		510 mm	4 kw	0,06 m/s	400 v / 50 hz	3.100 kg.	
	6.608 lbs	137,8 inch	137,8 inch	91,3x185 inch	112,2x204,7 inch	118,1x220,5 inch		20,1 inch	5,4 hp	2,4 inch/s	400 v / 50 hz	6.828 lbs	
TOTAL REX 30 GOLD	3.000 kg.	4.100 mm	4.100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4.000 kg.	
	6.608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	8.811 lbs	
TOTAL REX 25 GOLD + T	2.500 kg.	4.100 mm	4.100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5.800 kg.	T=tetto Corsa minima di 2800mm per denaa oltre 5600mm
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12.775 lbs	
TOTAL REX 20 GOLD + TP	2.500 kg.	4.100 mm	4.100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5.600 kg.	T=tetto Corsa minima di 2800mm per denaa oltre 5600mm
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12.335 lbs	
TOTAL REX 30 GOLD F	3.000 kg.	4.100 mm	4.100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4.100 kg.	F=flangiato
	6.608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	9.031 lbs	
TOTAL REX 25 GOLD F + T	2.500 kg.	4.100 mm	4.100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	6.000 kg.	F=flangiato T=tetto
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch	82,7 inch	20,31 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	13.216 lbs	
TOTAL REX 20 GOLD + TPF	2.500 kg.	4.100 mm	4.100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5.800 kg.	F=flangiato T=tetto P=piastrellabile
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12.775lbs	
TOTAL REX 60 PLATINUM	6.000 kg.	4.200 mm	4.200 mm	2650x5900 mm	3000x6000 mm	3000x7000 mm		800 mm	7,5 kw	0,07 m/s	400 v / 50 hz	6.000 kg.	
	13216 lbs	165,4 inch	165,4 inch	96,5x232,3 inch	118,1x236,2 inch	118,1x275,6 inch		31,5 inch	10,1 hp	2,8 inch/s	400 v / 50 hz	13.216 lbs	
TOTAL REX 40 PLATINUM +T	4.000 kg.	4.200 mm	4.200 mm	2650x5900 mm	3000x6000 mm	3000x7000 mm	2.100 mm	800 mm	7,5 kw	0,07 m/s	400 v / 50 hz	7.700 kg.	
	8.811 lbs	165,4 inch	165,4 inch	96,5x232,3 inch	118,1x236,2 inch	118,1x275,6 inch	82,7 inch	31,5 inch	10,1 hp	2,8 inch/s	400 v / 50 hz	16.960 lbs	
TOTAL REX 35 PLATINUM +TP	3.500 kg.	4.200 mm	4.200 mm	2650x5900 mm	3000x6000 mm	3000x7000 mm	2.100 mm	800 mm	7,5 kw	0,07 m/s	400 v / 50 hz	7.500 kg.	
	7.709 lbs	165,4 inch	165,4 inch	96,5x232,3 inch	118,1x236,2 inch	118,1x275,6 inch	82,7 inch	31,5 inch	10,1 hp	2,8 inch/s	400 v / 50 hz	16.520 lbs	